

Flowcal
 Unit 4
 Ham Business Centre
 Brighton Road
 Shoreham-by-Sea
 West Sussex
 BN43 6RE



Tel: 01273 455572
Fax: 01273 454120
Email:
 sales@flowcal.co.uk
Website:
 www.flowcal.co.uk



This thermometer is portable and easy to use. It is hand-held and non-contact. Simply aim and pull the trigger. The temperature of the item being measured will then be displayed in easy to read LCD format. Also featured on the LCD display, is a 'low battery' 'laser' and 'backlight' indication.

It comes with laser alignment as standard. This assists in the pin-pointing of the area to be measured.

This model is ideal for measuring surface temperatures, because it eliminates the need to touch the area or surface that you are measuring. It is not necessary to focus or calibrate the instrument, enabling it to be used by anyone.

Specification	8820 infrared thermometer
Range	-50 to +538°C
Resolution	0.1°C and 1°C or °F
Infrared Accuracy	± 5°C (-50 to -20°C)
Response Time	Approximately 1 second
Field of View	8:1 optics ratio (25mm minimum target)
Emissivity	Fixed at 0.95
Battery	9 volt MN 1604/PP3
Battery life	100 hours (without laser sighting)
Display	Custom LCD
Dimensions	45 x 90x 150mm
Weight	180 Grams
Price	£70.00

If you would like any more specific details about this range, please use the contact details above.

specification sheet specification sheet 8820 infrared thermometer